

Reprinted from

**Symposium on
Machine Processing of
Remotely Sensed Data**

June 29 - July 1, 1976

The Laboratory for Applications of
Remote Sensing

Purdue University
West Lafayette
Indiana

IEEE Catalog No.
76CH1103-1 MPRSD

Copyright © 1976 IEEE
The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org.

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

puter classification maps was smoothed, resulting in postprocessed maps that more closely resembled resource maps.

A NEW COMPUTER APPROACH TO MIXED FEATURE
CLASSIFICATION FOR FORESTRY APPLICATION*

E. P. Kan, J. K. Lo
Lockheed Electronics Company, Inc.
Aerospace Systems Division
Houston, Texas 77058

ABSTRACT

A new computer approach for mapping mixed forest features (i.e., classes, types) from computer classification maps is presented in both theory and application.

This approach is particularly useful and applicable to forestry stand mapping, where small areas are required to be absorbed into the surrounding to form "homogeneous" stands, and where mixed stands contain mixed proportions of different species of trees. Previous studies involving LANDSAT data show that mixed pine-hardwood stands are often erroneously classified as either pine or hardwood.

The present work utilizes a modification and an iterative application of a previously developed computer program called "CLEAN". The program CLEAN was tested on binary (2 classes, labeled 0 or 1) classification images.

The modification called "GETMIX" operates on a multi-class image and works on one prespecified class in any one application. In any iteration, small sets of pixels with labels other than the prespecified class are eliminated, while small sets of pixels of the prespecified class are retained and have their labels temporarily changed to a new unique class.

This new iterative approach was tested on LANDSAT-1 data over Sam Houston National Forest, and proved to be successful in mapping those mixed softwood/hardwood stands which were unidentifiable previously. Also due to the cleaning effect of the program GETMIX, the spotty appearance on com-

*The material of the paper was developed under NASA Contract NAS9-12200 and prepared for the Earth Observations Division, NASA/JSC, Houston, Texas.