

Reprinted from

**Symposium on
Machine Processing of
Remotely Sensed Data**

June 21 - 23, 1977

The Laboratory for Applications of
Remote Sensing

Purdue University
West Lafayette
Indiana

IEEE Catalog No.
77CH1218-7 MPRSD

Copyright © 1977 IEEE
The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org.

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

LANDSAT IMAGE ANALYSIS FOR TERRAIN INVESTIGATIONS

B. E. RUTH

Department of Civil Engineering
University of Florida
Gainesville, Florida, 32611

R. L. FERGUSON

General Electric Company
Daytona Beach, Florida

H. K. BROOKS

Department of Geology
University of Florida
Gainesville, Florida, 32611

A study was conducted to evaluate terrain conditions in the vicinity of Daytona Beach, Florida to facilitate selection of suitable landfill sites. LANDSAT computer compatible tapes (CCT's) were analyzed using various techniques available on the General Electric IMAGE 100 system. Atmospheric haze correction was performed by normalizing the hazy images to a standard spectral reflectance which was obtained for the Atlantic Ocean in the winter season scenes. Histogram analyses and the Image 100 (non-parametric) cellular, or parallelepiped, classification techniques were used to develop the bias necessary for atmospheric haze correction and also to establish the water signatures.

Various preprocessing techniques such as channel ratioing, normalization, and principle components (spectral) transformation were tested with split screen displays of scenes from different dates. This display format combined with channel and theme swapping between the quadrants was used for signature analysis and comparison. Slight shifts in registration affected the reliability of signatures developed from these techniques.

The most viable approach appeared to be the use of training sites for the development of reliable themes. Signatures were established for various categories in the different test scenes. Swamp and poorly drained areas with minimal vegetative cover were easily delineated for the different time periods, with some exceptions. Hardwood swamps containing bay, maple, and cabbage palm intermixed with cypress produced substantial shifts in the IR bands during the photo-synthesizing period. Flatwoods, planted pine, turkey oak, and the sandy ridge areas were not sufficiently separable spectrally to pro-

vide meaningful delineation. Lightly vegetated sandy soils did depict the lineation of relic beach ridges and other sandy, well drained zones.