

Reprinted from

Symposium on

Machine Processing of

Remotely Sensed Data

June 27 - 29, 1979

The Laboratory for Applications of
Remote Sensing

Purdue University
West Lafayette
Indiana 47907 USA

IEEE Catalog No.
79CH1430-8 MPRSD

Copyright © 1979 IEEE
The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org.

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

THE CONTROL POINT LIBRARY BUILDING SYSTEM

WAYNE NIBLACK

IBM Federal Systems Division

The Control Point Library Building System (CPLBS) is an interactive, menu-driven system which permits a user to accurately identify features in image data by simultaneously viewing a map and a vidicon display of the image data through a Zoom Transfer Scope, extract and store features in disk-resident libraries, and perform utility functions necessary to maintain and update the generated libraries. It was developed to permit the generation of control point libraries needed by the Master Data Processor (MDP) to perform highly accurate geometric corrections to Landsat MSS and RBV earth image data. Both CPLBS and MDP were developed by IBM under contract to NASA Goddard Space Flight Center and delivered in January 1979.

The CPLBS includes newly developed techniques for accurately locating control points which will perform consistently well in correlation uses, and for storing, updating, and refining sets of control points. It incorporates these techniques in a production system hosted on the MDP hardware, which includes a high-speed arithmetic processor, high-density asynchronous tape drives, and a large (1900 mbyte) on-line disk storage capacity. A Ramtek 9300 Display System and an IBM 3270 Display Station provide image and menu display capability.

This paper describes the host computer and special image viewing equipment, as well as the processing, accuracy, and throughput of the CPLBS, and the structure of the generated libraries.