

Reprinted from

Symposium on

Machine Processing of

Remotely Sensed Data

June 27 - 29, 1979

The Laboratory for Applications of
Remote Sensing

Purdue University
West Lafayette
Indiana 47907 USA

IEEE Catalog No.
79CH1430-8 MPRSD

Copyright © 1979 IEEE
The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org.

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

THE MONITORING OF MARINE ENVIRONMENTAL PROBLEMS BY AIRBORNE AND LANDSAT MSS DATA

HIROAKI OCHIAI

Toba Merchant Marine College

SHOJI TAKEUCHI

Remote Sensing Technology Center of Japan

For the purpose of monitoring of marine environmental problems, the authors tried digital analysis of multispectral scanner data obtained by airborne and Landsat around the coastal area of Japan.

The main purpose of this study is the detection of red tide which is popularly named after its apparent red color and caused by the abnormal growth of plankton. Due to the rapid increase of nutritious river water and industrial effluent into the sea, the frequency of red tide in coastal areas such as Tokyo Bay, Ise Bay and Seto Inland Sea increases year by year, and it becomes a serious social problem for fishing industry, especially fishing nursery industry.

In 1975, 1976 and 1978 several large-scale red tides occurred in Harimanada and Osaka Bay in a portion of Seto Inland Sea, and a large number of fish in the sea and in the fishing nursery were seriously damaged. In 1978, a severe red tide prevailed in Ise Bay for longer than two months, and almost all fish and shellfish in the coastal area were killed. Now, the detection and monitoring of red tide are among the most urgent needs for not only the fishing industry but also the administrative aspect for environmental problems.

Through this investigation, the authors found out the most effective wavelength for the detection of red tide is the thermal band of the airborne multispectral scanner. Although, unfortunately, the thermal band of Landsat-3 is not operated, the authors recognized that band-4 is also the most effective wavelength for the detection of red tide. The digital analysis of MSS data observed red tide was tried in several cases, and good results were carried out.