

Reprinted from

Symposium on

Machine Processing of

Remotely Sensed Data

June 27 - 29, 1979

The Laboratory for Applications of
Remote Sensing

Purdue University
West Lafayette
Indiana 47907 USA

IEEE Catalog No.
79CH1430-8 MPRSD

Copyright © 1979 IEEE
The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org.

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

AN UNSUPERVISED PROCEDURE USING MULTI-DIMENSIONAL HISTOGRAM INFORMATION

D.S. KAMAT, K. PADMANABHAN AND
K.L. MAJUMDAR

Space Applications Centre, India

Data obtained by Multispectral Scanner (MSS) or multiband photography for resources information extraction is usually very large. If this data has to be processed operationally, some fast processing techniques should be available. In this paper an unsupervised classification technique for processing MSS data is discussed.

The technique uses multidimensional histogram information (frequency) from multispectral digital data. The multidimensional histogram in this case may be considered as the summation of all the frequencies. A frequency may be considered to correspond to a class if it is greater than a predefined minimum number of population for a class. By comparing all the frequencies it is possible to get information about the probably classes existing in the area. Let there be N classes. Out of these N classes, some may not be distinct. The distinct classes can be obtained by defining a distance function and by specifying the tolerable distance between two classes. Once the distinct classes are known, the class centre is obtained by the weighted average. In this process class centres for M distinct classes are obtained. The whole area is classified into M classes and the classification is done on the basis of nearest neighbourhood criterion.

The above method is tested using ISRO-MSS five channel data for an area of 4.2 Kms x 4.2 Kms. The Bands used are 0.5 - 0.6 μm , 0.6 - 0.7 μm , 0.7 - 0.8 μm and 0.8 - 1.1 μm . The multidimensional histogram is obtained by quantizing the 0-255 grey levels to 0-15 levels and using look-up-table. An absolute distance function is used both for the combining of two classes and for classification. By appropriately defining the threshold for minimum population, a total of 19 probable classes are obtained. Further by specifying a threshold for inter-class distance, 9 classes are found to be

distinct. The results are presented in the form of tables and photo-thematic map. The classes obtained by the above method are verified by field checks.