

Reprinted from

Symposium on

Machine Processing of

Remotely Sensed Data

June 27 - 29, 1979

The Laboratory for Applications of
Remote Sensing

Purdue University
West Lafayette
Indiana 47907 USA

IEEE Catalog No.
79CH1430-8 MPRSD

Copyright © 1979 IEEE
The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org.

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

SMALL AREA REPLACEMENT IN DIGITAL THEMATIC MAPS

P. J. LETTS

DIPIX Systems, Ltd.

An algorithm is described for identifying small isolated areas in digital thematic maps and selectively replacing them with their (weighted) most frequently occurring neighbors. The identification process successively scans the thematic map in alternating directions (downward, upward, downward, etc.) until each pixel has been completely defined by the size of the area to which it belongs. The final output is an area size map which can be overlaid on the original thematic map. After the first (downward) scan only pixels at the bottom of individual areas are fully defined; after the second (upward) scan, all pixels which are connected in a continuously upward direction to the bottom of individual areas are fully defined; and so on. Spiral shaped areas require 1 scan for each semi-rotation or part of a semi-rotation. The replacement of selected areas is performed in a single simultaneous scan of the thematic map and the area size map. Pixels which lie in areas less than the specified minimum size for their corresponding themes are assumed to be unclassified, and the resulting unclassified areas are then replaced in successive steps. In each step the interior border pixels of the remaining unclassified area are replaced on an individual pixel basis by the most frequently occurring neighboring themes. Determination of the most frequently occurring neighbor can optionally include variable weighting for each theme and the algorithm also allows diagonally adjacent pixels to be connected or unconnected on a per scene basis.

This algorithm has been implemented in the ARIES image analysis system which was developed for the Canadian National Forest Institute. The limiting factor is the number of pixels per line and this implementation can cater for images with over 4000 pixels per line. The time taken to identify all areas less than 128 pixels

and to replace those of less than 4 pixels in a 16 class thematic map of 1000 lines by 1000 pixels was less than 15 minutes, including operator interaction.